



High power cycling capability
Low on-state and switching losses
Optimized for line frequency rectifiers
Designed for traction and industrial applications

**Power Rectifier
Avalanche Diodes
Type DA273-3200-36**

| | | | | |
|---------------------------------|------------|-----------|---------------|------|
| Average forward current | | I_{FAV} | 3200 A | |
| Repetitive peak reverse voltage | | V_{RRM} | 3000 ÷ 3600 V | |
| V_{RRM}, V | 3000 | 3200 | 3400 | 3600 |
| Voltage code | 30 | 32 | 34 | 36 |
| $T_j, °C$ | - 60 ÷ 175 | | | |

MAXIMUM ALLOWABLE RATINGS

| Symbols and parameters | | Units | Values | Test conditions |
|------------------------|----------------------------------|-------------------|---------------------|--|
| ON-STATE | | | | |
| I_{FAV} | Average forward current | A | 3200 3305 | $T_c=106 °C$; Double side cooled; $T_c=100 °C$; Double side cooled; 180° half-sine wave; 50 Hz |
| I_{FRMS} | RMS forward current | A | 5024 | $T_c=106 °C$; Double side cooled; 180° half-sine wave; 50 Hz |
| I_{FSM} | Surge forward current | kA | 42.0 50.0 | $T_j=T_{j,max}$ $T_j=25 °C$ 180° half-sine wave; $t_p=10$ ms; single pulse; $V_R=0$ V; |
| | | | 44.0 53.0 | $T_j=T_{j,max}$ $T_j=25 °C$ 180° half-sine wave; $t_p=8.3$ ms; single pulse; $V_R=0$ V; |
| I^2t | Safety factor | $A^2s \cdot 10^3$ | 8800 12500 | $T_j=T_{j,max}$ $T_j=25 °C$ 180° half-sine wave; $t_p=10$ ms; single pulse; $V_R=0$ V; |
| | | | 8000 11600 | $T_j=T_{j,max}$ $T_j=25 °C$ 180° half-sine wave; $t_p=8.3$ ms; single pulse; $V_R=0$ V; |
| BLOCKING | | | | |
| V_{RRM} | Repetitive peak reverse voltages | V | 3000÷3600 | $T_{j,min} < T_j < T_{j,max}$; 180° half-sine wave; 50 Hz; |
| $V_{(BR)}$ | Breakdown voltage | V | 3450÷4050 | $T_j=25 °C$; $I_{br}=100$ mA; $t_p = 10$ ms; 5 Hz |
| V_R | Reverse continuous voltages | V | $0.6 \cdot V_{RRM}$ | $T_j=T_{j,max}$; |
| P_{RSM} | Surge reverse power dissipation | kW | 16 | $T_j= T_{j,max}$; $t_p = 100$ μs; 180° half-sine current waveforms; single pulse |
| THERMAL | | | | |
| T_{stg} | Storage temperature | °C | - 60 ÷ 50 | |
| T_j | Operating junction temperature | °C | - 60 ÷ 175 | |
| MECHANICAL | | | | |
| F | Mounting force | kN | 40.0 ÷ 50.0 | |
| a | Acceleration | m/s^2 | 50 | Device clamped |


CHARACTERISTICS

| Symbols and parameters | | Units | Values | Conditions |
|------------------------|---|---------------------------|------------------|---|
| ON-STATE | | | | |
| V_{FM} | Peak forward voltage, max | V | 2.20 | $T_j=25\text{ }^\circ\text{C}; I_{FM}=10048\text{ A}$ |
| $V_{F(TO)}$ | Forward threshold voltage, max | V | 1.05 | $T_j=T_{j\text{ max}};$ |
| r_T | Forward slope resistance, max | m Ω | 0.200 | $0.5\pi I_{FAV} < I_T < 1.5\pi I_{FAV}$ |
| BLOCKING | | | | |
| I_{RRM} | Repetitive peak reverse current, max | mA | 150 | $T_j=T_{j\text{ max}};$ $V_R=V_{RRM}$ |
| SWITCHING | | | | |
| Q_{rr} | Total recovered charge, max | μC | 5550 | $T_j=T_{j\text{ max}}; I_{TM}=1500\text{ A};$ |
| t_{rr} | Reverse recovery time, max | μs | 75.0 | $di_R/dt=-5\text{ A}/\mu\text{s};$ |
| I_{rrM} | Peak reverse recovery current, max | A | 148 | $V_R=100\text{ V};$ |
| THERMAL | | | | |
| R_{thjc} | Thermal resistance, junction to case, max | $^\circ\text{C}/\text{W}$ | 0.0082 | Double side cooled |
| R_{thjc-A} | | | 0.0187 | Anode side cooled |
| R_{thjc-K} | | | 0.0153 | Cathode side cooled |
| R_{thck} | Thermal resistance, case to heatsink, max | $^\circ\text{C}/\text{W}$ | 0.0020 | Direct current |
| MECHANICAL | | | | |
| w | Weight, max | g | 1500 | |
| D_s | Surface creepage distance | mm (inch) | 41.40 (1.630) | |
| D_a | Air strike distance | mm (inch) | 23.10 (0.909) | |

PART NUMBERING GUIDE

| | | | | |
|----|-----|------|----|---|
| DA | 273 | 3200 | 36 | N |
| 1 | 2 | 3 | 4 | 5 |

1. DA — Avalanche Diode
2. Design version
3. Average forward current, A
4. Voltage code
5. Ambient conditions: N – normal; T – tropical



All dimensions in millimeters (inches)




Fig 1 – Forward characteristics of Limit device

Analytical function for Forward characteristic:

$$V_F = A + B \cdot i_F + C \cdot \ln(i_F + 1) + D \cdot \sqrt{i_F}$$

| | Coefficients for max curves | |
|----------|-----------------------------|-------------------------|
| | $T_j = 25^\circ\text{C}$ | $T_j = T_{j\text{max}}$ |
| A | -0.27916000 | 0.10736000 |
| B | 0.00010897 | 0.00016001 |
| C | 0.20615000 | 0.08469000 |
| D | -0.00511710 | 0.00595080 |

Forward characteristic model (see Fig. 1).




Fig 2 – Transient thermal impedance Z_{thjc} vs. time t

Analytical function for Transient thermal impedance junction to case Z_{thjc} for DC:

$$Z_{thjc} = \sum_{i=1}^n R_i \left(1 - e^{-\frac{t}{\tau_i}} \right)$$

Where $i = 1$ to n , n is the number of terms in the series.

t = Duration of heating pulse in seconds.

Z_{thjc} = Thermal resistance at time t .

R_i = Amplitude of p_{th} term.

τ_i = Time constant of r_{th} term.

DC Double side cooled

| i | 1 | 2 | 3 | 4 | 5 | 6 |
|--------------|------------|----------|-----------|----------|------------|----------|
| R_i , K/W | 0.00007989 | 0.002673 | 0.0005936 | 0.000846 | 0.00005975 | 0.003948 |
| τ_i , s | 1.688 | 0.06219 | 0.002329 | 0.138 | 0.0003243 | 0.9533 |

DC Cathode side cooled

| i | 1 | 2 | 3 | 4 | 5 | 6 |
|--------------|----------|----------|-----------|----------|-----------|------------|
| R_i , K/W | 0.006619 | 0.004034 | 0.0008595 | 0.002956 | 0.0005965 | 0.00005689 |
| τ_i , s | 9.744 | 1.025 | 0.1394 | 0.06237 | 0.002318 | 0.0003037 |

DC Anode side cooled

| i | 1 | 2 | 3 | 4 | 5 | 6 |
|--------------|---------|----------|-----------|----------|-----------|------------|
| R_i , K/W | 0.01013 | 0.004062 | 0.0009401 | 0.002853 | 0.0005963 | 0.00005641 |
| τ_i , s | 9.747 | 1.058 | 0.1304 | 0.06179 | 0.002313 | 0.0003013 |

Transient thermal impedance junction to case Z_{thjc} model (see Fig. 2)




Fig 3 – Maximum recovered charge Q_{rr-i} (integral) vs. commutation rate di_R/dt




Fig 4 – Maximum recovered charge Q_{rr} vs. commutation rate di_R/dt (25% chord)




Fig 5 – Maximum reverse recovery current I_{rrM} vs. commutation rate di_R/dt




Fig 6 – Maximum recovery time t_{rr} vs. commutation rate di_R/dt (25% chord)




Fig. 7 - Mean forward power dissipation P_{FAV} vs. mean forward current I_{FAV} for sinusoidal current waveforms at different conduction angles (f=50Hz, DSC)




Fig. 8 - Mean forward power dissipation P_{FAV} vs. mean forward current I_{FAV} for rectangular current waveforms at different conduction angles and for DC (f=50Hz, DSC)




Fig. 9 – Mean forward current I_{FAV} vs. case temperature T_c for sinusoidal current waveforms at different conduction angles ($f=50\text{Hz}$, DSC)




Fig. 10 - Mean forward current I_{FAV} vs. case temperature T_c for rectangular current waveforms at different conduction angles and for DC ($f=50\text{Hz}$, DSC)




Fig. 11 – Maximum surge forward current I_{FSM} and safety factor I^2t vs. pulse length t_p




Fig. 12 - Maximum surge forward current I_{FSM} vs. number of pulses n_p