



High power cycling capability
Low on-state and switching losses
Optimized for line frequency rectifiers
Designed for traction and industrial applications

Rectifier Diode
Type D233-1000-18

Average forward current			I _{FAV}	1000 A				
Repetitive peak reverse voltage			V _{RRM}	1000 ÷ 1800 V				
V _{RRM} , V	1000	1100	1200	1300	1400	1500	1600	1800
Voltage code	10	11	12	13	14	15	16	18
T _j , °C				-60 ÷ 190				

MAXIMUM ALLOWABLE RATINGS

Symbols and parameters		Units	Values	Test conditions		
ON-STATE						
I _{FAV}	Average forward current		A	1000 1155	T _c =117 °C; Double side cooled; T _c =100 °C; Double side cooled; 180° half-sine wave; 50 Hz	
I _{FRMS}	RMS forward current		A	1570	T _c =117 °C; Double side cooled; 180° half-sine wave; 50 Hz	
I _{FSM}	Surge forward current	kA	16.0 18.0	T _j =T _j max T _j =25 °C	180° half-sine wave; 50 Hz (t _p =10 ms); single pulse; V _R =0 V;	
			17.0 20.0	T _j =T _j max T _j =25 °C	180° half-sine wave; 60 Hz (t _p =8.3 ms); single pulse; V _R =0 V;	
I ² t	Safety factor	A ² s·10 ³	1280 1620	T _j =T _j max T _j =25 °C	180° half-sine wave; 50 Hz (t _p =10 ms); single pulse; V _R =0 V;	
			1195 1660	T _j =T _j max T _j =25 °C	180° half-sine wave; 60 Hz (t _p =8.3 ms); single pulse; V _R =0 V;	
BLOCKING						
V _{RRM}	Repetitive peak reverse voltages		V	1000÷1800	T _{j min} < T _j <T _j max; 180° half-sine wave; 50 Hz;	
V _{RSM}	Non-repetitive peak reverse voltages		V	1100÷1900	T _{j min} < T _j <T _j max; 180° half-sine wave; 50 Hz;single pulse;	
V _R	Reverse continuous voltages		V	0.75·V _{RRM}	T _j =T _j max;	
THERMAL						
T _{stg}	Storage temperature		°C	-60÷50		
T _j	Operating junction temperature		°C	-60÷190		
MECHANICAL						
F	Mounting force		kN	9.0÷11.0		
a	Acceleration		m/s ²	50 100	Device unclamped Device clamped	


CHARACTERISTICS

Symbols and parameters		Units	Values	Conditions	
ON-STATE					
V _{FM}	Peak forward voltage, max	V	1.60	T _j =25 °C; I _{FM} =3140 A	
V _{F(TO)}	Forward threshold voltage, max	V	0.95	T _j =T _{j max} ; V _R =V _{RRM}	
r _T	Forward slope resistance, max	mΩ	0.350	0.5 π I _{FAV} < I _T < 1.5 π I _{FAV}	
BLOCKING					
I _{RRM}	Repetitive peak reverse current, max	mA	50	T _j =T _{j max} ; V _R =V _{RRM}	
THERMAL					
R _{thjc}	Thermal resistance, junction to case, max	°C/W	0.040	Direct current	Double side cooled
R _{thjc-A}			0.088		Anode side cooled
R _{thjc-K}			0.072		Cathode side cooled
R _{thck}	Thermal resistance, case to heatsink, max	°C/W	0.008	Direct current	
MECHANICAL					
w	Weight, typ	g	180		
D _s	Surface creepage distance	mm (inch)	23.69 (0.933)		
D _a	Air strike distance	mm (inch)	19.10 (0.752)		

PART NUMBERING GUIDE

D	233	1000	18	N
1	2	3	4	5

1. D — Rectifier Diode
2. Design version
3. Average forward current, A
4. Voltage code
5. Ambient conditions: N – normal; T – tropical

OVERALL DIMENSIONS**Package type: D.B2**

All dimensions in millimeters (inches)

The information contained herein is confidential and protected by Copyright.
In the interest of product improvement, Proton-Electrotex reserves the right to change data sheet without notice.